Relational Products



KET 101UE/M Card Issuer

Dimension: L114×W75×H17(mm); Streamline design and good-looking;
Working Frequency: 125KHz/13.56MHz;
Delay of reading card: less than 0.1s;
Temperature: -20℃~60℃;
Humidity: 5%~90%; PCB 100% waterproof;
Communication Interface: standard RS232, compatible with RS232 of EIA/TIA, +/-15KV ESD's protection(static prohibit discharge), fixed transmission velocity is 9600BPS;
Max Reading Range: EM 150mm (in ideal condition), Mifare 80mm (in ideal condition);
Transmission Distance: ≤15M;
Working State: voice and light working state, red light for standby, green light and DI-DI prompt for reading card.




KET101UMW Card Issuer

Dimension: L114×W75×H17(mm);
Weight: 55g;
Colour: Gray;
Working Frequency: 13.56MHz;
Delay of reading card: less than 0.1s;
Temperature: -20℃~60℃;
Humidity: 5%~90%; PCB 100% waterproof;
Communication Interface: standard RS232, compatible with RS232 of EIA/TIA, +/-15KV ESD's protection(static prohibit discharge), fixed transmission velocity is 38400BPS;
Transmission Distance: ≤15M.



KET 485 HUB Switcher

Dimension: L270 xW160 xH54 (mm);
IPower supply: AC 220V 10% with 12V/3A switch powe;
Working current: 70mA for standby; less than 200mA for working condition (below12V);
Working Temperature: -20℃~60℃;
Humidity: 5%~90%;
Protective measures: Ensuring safety of ports by means of over current protection (Anti-fuse), 75V lightningproof, TVS safeguard and model protection;
Condition indication: green light lighting up for normal standby, yellow light flashing for normal communication
Function Character: 4-line RS485 input, 1-line RS485 expand output and 1-line RS232 output, independence for each other, do not interfered others.



KET 485 Switcher

Dimension: L105 xW 32x H12.5 (mm);
IPower supply: RS232 bunch fetches the electricity;
IInterface Protection: +/-15V ESD static current protection, excessive pressure protection and lightningproof measure;
Working Temperature: -20℃~60℃;
Humidity: 5%~90%;
Communication Interface: RS485/RS232.



KET 102C Electric-lock

Standard Voltage: DC 12V with polarity protection of reverse;
Startup Current: 0.9A;
Waiting Current: keep working with 0.3A;
Safety Precautions: lock for electrify and open for power off;
Auto-lock: 0-5 (second);
Dimension (standard): L200 xW34 xH 42 (mm);
Bolt: diameter 15.5mm;
Weight: 0.9Kg;
Suit for: wood door, glass door.



KET 102A Magnet-lock

Bearing: 280-300 Kg;
Dimension (standard): L185 x W38 x H12.5 (mm);
Standard Voltage: DC 12V/24V;
Signal Feedback: locked, magnet-door;
Attraction Current: 500mA/12V, 250mA/24V;
Indicator Light: display state of LBD;
Suit for: wood door, iron door, glass door;



KET 102D Pulse-lock

Mode of open: pulse signal;
Safety Precautions: open the lock for electrify;
Standard Voltage: DC 12V;
Working Current: 1000mA;
Install Direction: right (from outside to inside, ascertain the left and right accord to door hinge; push the door is front, pull the door is back; the lock install on the door);
Suit for: iron door.



KET 102J Cathode-lock

Standard Voltage: DC 12V;
Safety Precautions: open the lock for electrify or Power off;
Bolt: Max length 3/4″;
Dimension of stainless steel plank:
Short Type: 1—1/4″ x 4—7/8″ (31.7x123.7mm)
Long Type: 1—1/4″ x 6—7/8″ (31.7x174.5mm);
Suit for: wood door.



