
Category **Loudspeakers**

Code **TR20-HF**

Range **Horns with built-in unit**



Description

16 W Horn Loudspeaker


Two-way horn loudspeaker made of reinforced polypropylene, self-extinguishing rating UL94-VO. The class of mechanical protection of the assembly as a whole is IP44.
It consists of a curved horn fed by a cone type loudspeaker (mid-woofer) and by a compression unit (tweeter) coupled with a dome-type unit. A cross-filter separates the frequencies to be sent to the two loudspeakers. This particular shape determines an almost constant and controlled coverage of the sound spectrum, ensuring high efficiency of the speaker unit (typical of a horn speaker unit) and at the same time a broad frequency response. The input transformer for connection to constant-voltage lines is fitted with sockets for adjusting the output power delivered.

Technical data


Rated output power	16 W
Adjustable output power	16 - 8 - 4 W
Line voltage	50 - 70 - 100 V
Frequency response	110 ÷ 20.000 Hz
Efficiency (1W/1m)	102 dB
Acoustic pressure (Pnom/1m)	116 dB
Horizontal dispersion angle (2 kHz)	45°
Vertical dispersion angle (2 kHz)	80°
Weight	4,2 kg

Polar diagrams (2 kHz)


• Horizontal curve •



• Vertical curve •



Layout dimensions



PASO S.p.A. reserve the right to make changes to the drawings and specifications at any time and without notice.